



# RACING



LucasOil.com • (800) 342-2512





# RACING

## RACING ENGINE OIL

### RACING ONLY ENGINE OILS



- High ZINC fortified
- Perfect oil for high RPM engines
- Extra protection
- Lower oil temperature
- Less drag for more horsepower!
- Compatible with methanol or racing gas

SAE 20W-50	
1 Quart	10620
5 Quart	10621
5 Gal Pail	10623
55 Gal Drum	10624
SYN SAE 5W-20	
1 Quart	10883
5 Quart	10884
5 Gal Pail	10944
55 Gal Drum	10948
SYN SAE 5W-30	
1 Quart	10885
5 Quart	10886
5 Gal Pail	10945
55 Gal Drum	10949

SYN SAE 5W-50	
1 Quart	10101
5 Gal Pail	10382
55 Gal Drum	10384
SYN SAE 10W-40	
1 Quart	10942
5 Quart	10911
5 Gal Pail	10912
55 Gal Drum	10950
SYN SAE 20W-50	
1 Quart	10615
5 Quart	10616
5 Gal Pail	10618
55 Gal Drum	10619



### PLUS RACING ONLY ENGINE OILS

- Has extra additives over and above regular racing oils
- Resists breakdown from racing fuel contamination
- Resists oxidation and thinning out at high crank-case temperatures
- Contains a high level of detergents and dispersants
- Resists sludge and varnish formations

SAE 50 PLUS	
1 Quart	10347
5 Gal Pail	10095
55 Gal Drum	10107
SAE 60 PLUS	
1 Quart	10910
5 Gal Pail	10697
55 Gal Drum	10696
70 PLUS	
1 Quart	10348
5 Gal Pail	10266
55 Gal Drum	10268

# RACING



## SEMI-SYNTHETIC RACING ONLY ENGINE OILS

- Fortified with extra ZINC for severe racing applications
- Resists breakdown and contamination from exotic fuels such as nitro and methanol
- Resists thinning out at high crank-case temperatures

SEMI-SYN SAE 10W-40	
1 Quart	10943
5 Quart	10913
5 Gal Pail	10914
55 Gal Drum	10951
SEMI-SYN SAE 20W-50	
1 Quart	10306
5 Quart	10378
5 Gal Pail	10604
55 Gal Drum	10310



## JUNIOR DRAGSTER RACING OIL SYNTHETIC SAE 5W-20

- 100% synthetic
- An ultra-light viscosity 5W-20 motor oil
- Excellent protection
- Maximum horsepower gain
- No dry starts
- Lower oil temperatures
- Less friction

U.S. Measure	Product Number
15 oz	10380
5 Quart	10471



## ENGINE BREAK-IN OILS

- Quicker more efficient ring seal
- Higher levels of zinc and phosphorus maximum protection
- A must use for flat tappet camshaft break-in
- Less blow-by equates more power and better ring seal
- Requires no moly supplement and no additional additives
- Compatible with methanol and high octane race fuel
- Recommended use on initial break-in of both flat tappet and roller camshaft applications for maximum protection and performance
- Excellent on track performance prior to switching engine over to the racing only line conventional or synthetic

SAE 30 PLUS	
1 Quart	10630
5 Quart	10631
5 Gal Pail	10633
55 Gal Drum	10634
SAE 5W-20	
1 Quart	11033
5 Quart	11034
5 Gal Pail	11035
55 Gal Drum	11036
SAE 20W-50	
1 Quart	10635
5 Quart	10636
5 Gal Pail	10638
55 Gal Drum	10639



# RACING

## RACING SUSPENSION FLUID



### RACING SUSPENSION FLUIDS

- Superior Damping
- Controls Heat
- Lower Operating Temperatures
- Excellent Thermal Stability
- Contains special anti-wear and lubricity agents
- Excellent for high performance and heavy-duty applications

S1	
1 Quart	10488
5 Quart	10548
5 Gal Pail	10550
S2	
1 Quart	10489
5 Quart	10552
5 Gal Pail	10554

## 2-CYCLE OILS



### RACING FORMULA SYNTHETIC 2-CYCLE OIL

- 100% synthetic
- An ultra-light viscosity 5W-20 motor oil
- Excellent protection
- Maximum horsepower gain
- No dry starts
- Lower oil temperatures
- Less friction

U.S. Measure	Product Number
1 Quart	10828
1 Gallon	10829



### SEMI-SYNTHETIC TC-W3<sup>®</sup> 2-CYCLE LAND & SEA OIL

- Surpasses Mercury, Evinrude and Johnson Motors requirements
- Expect longer ring life, less fuel consumption and no filter clogging
- Excellent rust protection
- Prevents piston and cylinder scuffing
- Meets or exceeds industry performance requirements

U.S. Measure	Product Number
1 Quart	10467
1 Gallon	10557
5 Gal Pail	10469
55 Gal Drum	10470

## RACING GEAR OIL

### RACING GEAR OILS

**L9 - Differentials & Transmissions**

**L10 - Transmissions**

**L11 - Quick Qualifier**

- Perfect for super speedways
- Increases usable horsepower to the ground by reducing drag and friction
- Contains special anti-wear and lubricity agents
- Special synthetic base stocks
- Very thermal stable

L9	
1 Quart	10456
5 Gal Pail	10458
L10	
5 Gal Pail	10462
L11	
5 Gal Pail	10540



### SYNTHETIC SAE 140 & 250 RACING GEAR OILS

- Reduced oil temps in rear differentials
- Excellent thermal and shear stability
- Extends component life

SYN SAE 140	
5 Quart	10431
5 Gal Pail	10433
SYN SAE 250	
5 Quart	10646
5 Gal Pail	10648







# RACING

## ENGINE OIL ADDITIVES



### HEAVY DUTY OIL STABILIZER

- Increases oil life at least 50% longer
- Reduces oil consumption
- Eliminates dry starts
- Raises oil pressure
- Increases power and miles per gallon

U.S. Measure	Product Number
<b>1 Quart</b>	<b>10001</b>
<b>1 Gallon</b>	<b>10002</b>
<b>5 Gal Pail</b>	<b>10015</b>
<b>16 Gal Keg</b>	<b>10085</b>
<b>55 Gal Drum</b>	<b>10091</b>
<b>330 Gal Tote</b>	<b>10398</b>



### PURE SYNTHETIC OIL STABILIZER

- Increases oil life at least 50% longer
- Reduces oil consumption
- Eliminates dry starts
- Raises oil pressure
- Increases power and miles per gallon

U.S. Measure	Product Number
<b>1 Quart</b>	<b>10130</b>
<b>1 Gallon</b>	<b>10131</b>
<b>5 Gal Pail</b>	<b>10132</b>
<b>16 Gal Keg</b>	<b>10133</b>
<b>55 Gal Drum</b>	<b>10134</b>
<b>330 Gal Tote</b>	<b>11133</b>



### LOW VISCOSITY STABILIZER

- Improves fuel economy and power
- FRICTION REDUCTION
- Provides wear reduction
- Improvement in oxidation resistance
- Improvement with dispersancy which reduces deposits and varnish
- Improves premium quality motor oil
- Eliminates dry starts, the #1 cause of wear in new engines

U.S. Measure	Product Number
<b>12 oz</b>	<b>11097</b>



## TB ZINC PLUS ENGINE BREAK-IN OIL ADDITIVE

- Protects camshaft lifters and valve train during break-in period of motor
- Excellent for flat tappet camshafts during break-in or as an additive to any motor oil to prevent premature wear
- Add one bottle with every oil change to increase the zinc content of your motor oil
- Designed for race applications requiring additional extreme pressure additives
- Dyno testing shows a more efficient break-in when used resulting in less engine run time prior to race day
- Exclusive blend of extreme pressure additives
- Not designed for passenger car use

U.S. Measure	Product Number
16 oz	10063
55 Gal Drum	10472

## FUEL TREATMENTS



## OCTANE BOOSTER

- Safe for turbos, oxygen sensors and catalytic converters
- Suitable for use in fuel injected and carbureted engines
- Provides more boost than most other brands
- Promotes clean fuel burn for fewer emissions

U.S. Measure	Product Number
2 oz	10725
5.25 oz	10930
15 oz	10026



## DEEP CLEAN FUEL SYSTEM CLEANER

- Greatly reduces harmful NOx emissions
- Removes carbon deposits
- Totally eliminates knocking and pinging
- Raises MPG and performance

U.S. Measure	Product Number
5.25 oz	10669
16 oz	10512
55 Gal Drum	10575



# RACING

## PROBLEM SOLVERS

### ASSEMBLY LUBE



- Eliminates dry starts
- Perfect for engine building
- Use to pre lube bearings, cams, lifters and valve train
- Prevents seizing galling and scuffing
- Compatible with all oils
- Super slick and tacky
- Prevents breakdown during long term storage
- Contains ZINC, MOLY and other high pressure additives
- Easy to use

U.S. Measure	Product Number
4 oz	10152
8 oz	10153
5 Gal Pail	10390
55 Gal Drum	10559

### SUPER COOLANT



- Lower cylinder head temps
- Allow advanced ignition, timing and more horsepower
- Reduce operating temperatures by up to 20° F
- Prevents corrosion, electrolytes and deposits that cause leaks, overheating, and cooling system failures

U.S. Measure	Product Number
16 oz	10640

### BRAKE PARTS CLEANER



- High quality components to provide excellent performance
- Effectively removes brake fluid, grease, dust, and more
- For use on all ABS, disc, and drum brakes
- Quiets noise associated with excessive brake dust

U.S. Measure	Product Number
14 oz net	10906

### SYNTHETIC BRAKE FLUID DOT 3 & DOT 4



- Prevents seal hardening or softening
- Protects against rust or corrosion
- Provides excellent lubricity
- Compatible with all brake system rubber components and other fluids

DOT 3	
12 oz	10825
1 Quart	10826
DOT 4	
12 oz	10827





# RACING



## SPROCKET & CHAIN LUBE

- Water resistant
- Heat resistant
- Resist slinging
- Less friction
- Provides excellent anti-rust protection

U.S. Measure	Product Number
4 oz	10525



## CHAIN LUBE AEROSOL

- Designed to penetrate deeply into pins and bushing of the chains
- Excellent rust and corrosion inhibitor, as well as water resistant
- Leaves protective film to ensure minimum wear and drag
- Suitable for use on all chains including O-ring types

U.S. Measure	Product Number
11 oz net	10393



## CONTACT CLEANER AEROSOL

- Superior cleaning and drying formula
- Greater value compared to competitors products
- Made in U.S.A.

U.S. Measure	Product Number
14 oz net	10799



## PENETRATING OIL

- A truly superior penetrant designed to dissolve corrosion and rust without drying
- Provides a microscopic film that rust proofs for up to a year inside or out
- Excellent protection against water, even salt water
- Fortified with anti-seize agents
- Low odor

U.S. Measure	Product Number
11 oz net	11043



# RACING

## MULTI-PURPOSE PARTS CLEANER & DEGREASER



- Formulated with advanced Polyetheramine (PEA) detergents to clean and degrease carburetors, chokes, brake calipers, rotors, air intakes, throttle bodies and unpainted metal parts
- Removes any build-up that can cause loss of power, rough idle, high emissions and hard starting
- Helps remove unwanted deposits such as gum, varnish, oil, brake fluid, grease, dirt and sludge
- Cleans brakes for better performance and smoother operation
- Fast drying
- Will not harm catalytic converters and oxygen sensors
- Does not contain CFC's or chlorinated solvents
- 50 state VOC compliance

U.S. Measure	Product Number
16 oz net	11115

## GREASES

## EXTREME PRESSURE SYNTHETIC GREASE



- Greatly reduces friction on moving parts to prevent galling
- Excellent adhesion quality
- Excellent on all surfaces requiring an extreme pressure lubricant
- Perfect for assembly lube on rod bolts
- Protects pushrod ends on initial start up
- Essential for roller lifters, rockers, pushrods and camshafts

U.S. Measure	Product Number
1 oz tube	10563

## RACING ASSEMBLY GREASE



- Provides protection during initial start-up
- Designed for use on cams and lifters
- Dissolves completely in oil
- Provides excellent rust and corrosion protection

U.S. Measure	Product Number
5/8 oz	10921
16 oz	10891



## APPEARANCE PRODUCTS



### SLICK MIST® SPEED WAX

- Premium paint gloss intensifier
- Great for cars, trucks, boats, and airplanes
- Shines and protects in one easy application
- Excellent results on chrome, glass and vinyl decals
- Use on wet or dry surfaces
- Quick and easy
- Ease of application

U.S. Measure	Product Number
12 Pk - 24 oz	10160
6 Pk - 24 oz	10160-6
2 oz	10161



### SLICK MIST® INTERIOR DETAILER

- Restores interior
- Long lasting
- Non-oily formula
- Sling resistant
- UV resistant / protection
- Ease of application
- Over spray not a problem
- Water based
- pH Neutral (7-8)
- Quick and easy
- Great for cars, trucks, boats, and airplanes
- Shines and protects in one easy application

U.S. Measure	Product Number
24 oz	10514



### SLICK MIST® TIRE & TRIM SHINE

- Water based
- Quick and easy
- Long lasting
- Sling resistant
- UV resistant
- Prevents side-wall blowout
- Great for cars, trucks, boats, and airplanes
- Shines and protects in one easy application
- Over spray not a problem

U.S. Measure	Product Number
24 oz	10513
2 oz	10104



### METAL POLISH

- Polishes and cleans all metals (aluminum, chrome, magnesium, stainless steel, silver, brass, gold)
- Easy to use and safe for all metals
- No acids or ammonia

U.S. Measure	Product Number
16 oz	10155





**(800) 342-2512**

**[LucasOil.com](http://LucasOil.com)**