

SXS PREMIUM ENGINE

HIGH PERFORMANCE 4-STROKE ENGINE OIL

DESCRIPTION:

Mineral based 4-stroke engine oil specifically formulated for side-by-side (SXS) engines. Shear-stable polymer system provides excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system reduces temperatures and increases power output while keeping your engine running clean, trouble-free and extending the life of the machine. Exceeds the requirements of API SL / JASO MA2.

FEATURES & BENEFITS:

- Recommended for use in all OEM equipment
- Formulated specifically for SXS engines
- Superior protection at any temperature
- Reduces temperature and increases power output
- Shear-stable formula maintains oil viscosity and film thickness
- Optimizes cleanliness while controlling oxidation and wear
- Exceeds API SL and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled SXS 4-stroke gasoline engines.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	10W-40
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	90.3
VISCOSITY @ 100°C (cSt)	D445	13.5
VISCOSITY INDEX	D2270	151
FLASH POINT (°C)	D92	220
POUR POINT (°C)	D97	-39
DENSITY @ 15 °C (g/ml)	D4052	0.867