



## Mobil™ Full Synthetic High Mileage

Mobil Passenger-Vehicle-Lube , United States

Full Synthetic Motor Oil

### Product Description

Mobil™ Full Synthetic High Mileage motor oils protect critical engine parts 1.5 times longer than our conventional and synthetic blend oils\*, while helping to extend engine life in vehicles with over 75,000 miles. These full synthetic formulations are designed for higher mileage vehicles, both engines requiring a full synthetic motor oil and vehicles that are upgrading from conventional and synthetic blend oils. Mobil Full Synthetic High Mileage motor oils meet or exceed the latest industry performance requirements and meet warranty requirements for cars, trucks and SUVs with gasoline engines.

### Features and Benefits

Mobil™ Full Synthetic High Mileage motor oils deliver guaranteed protection that's 1.5 times longer than our conventional and synthetic blend oils. These oils have been tested and proven to provide long lasting protection to help extend engine life.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Formulation with balanced additive system	Outperforms our conventional oil
Excellent resistance to oil breakdown	Proven long lasting Protection
Helps prevent sludge & deposit formation and engine wear	Helps extend engine life
Maintains oil viscosity even in high operating temperatures	Helps control oil thickening and breakdown
Warranty	Limited Warranty* offers protection for up to 7,500 miles or your vehicle's recommended oil change interval, whichever is longer

### Applications

Mobil™ Full Synthetic High Mileage motor oils are recommended by ExxonMobil for all types of gasoline-powered vehicles, including turbocharged engines, found in passenger cars, SUVs and light-duty vans and trucks.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

### Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL FULL SYNTHETIC HIGH MILEAGE 0W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-30
FORD WSS-M2C945-A		X	
Ford WSS-M2C930-A		X	
FORD WSS-M2C946-A			X

This product is recommended for use in applications requiring:	MOBIL FULL SYNTHETIC HIGH MILEAGE 0W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-30
Ford WSS-M2C929-A			X
FORD WSS-M2C947-A	X		
Ford WSS-M2C947-B1	X		
FORD WSS-M2C960-A1		X	
FORD WSS-M2C961-A1			X
FORD WSS-M2C962-A1	X		

This product meets or exceeds the requirements of:	MOBIL FULL SYNTHETIC HIGH MILEAGE 0W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-30
API SJ	X	X	X
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
Ford WSS-M2C945-A	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X	X	X
API SP	X	X	X
API SP Resource Conserving	X	X	X
ILSAC GF-6A	X	X	X
CHRYSLER MS-6395	X	X	X

#### Properties and Specifications

Property	MOBIL FULL SYNTHETIC HIGH MILEAGE 0W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-30
Grade	SAE 0W-20	SAE 5W-20	SAE 5W-30
Density @ 15 C, g/ml, ASTM D4052	0.851	0.852	0.852
Flash Point, °C, ASTM D92	223	223	225
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.3	8.3	11.5

Property	MOBIL FULL SYNTHETIC HIGH MILEAGE 0W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-20	MOBIL FULL SYNTHETIC HIGH MILEAGE 5W-30
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45	46	65
Pour Point, °C, ASTM D97	-39	-42	-39

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

### Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved