



RED LINE 15W50 MOTOR OIL



- Popular in turbocharged applications
- For wider bearing clearances and racing engines that see occasional street use
- 25% more viscosity than petroleum 20W-50s.
- Not recommended for use in cold climates (-20°C/-5°F for 15W50)

RECOMMENDED FOR:

API SN/SM/SL/SJ/SH/SG/CF
ACEA A3/B3/B4

TYPICAL PROPERTIES:

ACEA Service Class	A3 B3/B4
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	15W50
Vis @ 100°C, cSt	19.6
Vis @ 40°C, cSt	138
Viscosity Index	162
CCS Viscosity, Poise, @ °C	65@-20
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @150°C, ASTM D4741	5.8

PACKAGE SIZES:

- 11504 - 15W50 Motor Oil - quart
- 11505 - 15W50 Motor Oil - gallon
- 11506 - 15W50 Motor Oil - 5 gallon
- 11508 - 15W50 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the Safety Data Sheet at REDLINEOIL.COM