



RED LINE 5WT DRAG RACE OIL (0W5)



- Popular for class racing in NHRA Stock and Super Stock
- Use only at oil temperatures below 160°F
- Also popular in NHRA Competition Eliminator

TYPICAL PROPERTIES:

| | |
|--|----------|
| Vis @ 100°C, cSt | 4.6 |
| Vis @ 40°C, cSt | 21.8 |
| Viscosity Index | 134 |
| CCS Viscosity, Poise, @ °C | 20@-30°C |
| Pour Point, °C | -54 |
| Pour Point, °F | -65 |
| Zinc, avg PPM | 2400 |
| Phosphorus, avg PPM | 3350 |
| NOACK Evaporation Loss, 1hr @ 482°F (250°C), % | 12 |

PACKAGE SIZES:

- 10004 - 5WT Race Oil - quart
- 10005 - 5WT Race Oil - gallon
- 10006 - 5WT Race Oil - 5 gallon
- 10008 - 5WT Race Oil - 55 gallon

ABOUT RED LINE MOTOR OIL FOR RACING

- Reformulated for improved frictional properties
- Special detergents for improved lubricity and less detonation
- Polyol ester base stocks provide more stability and film strength when exposed to excess fuel dilution
- Each of these products has no less than 2200ppm of zinc and phosphorus for antiwear
- Each race oil product is a multi-grade, offering 2-4% more power than oil of a similar viscosity - 20WT is a 5W20, 30WT is a 10W30, 40WT is a 15W40, 50WT is a 15W50
- Improved protection at startup, lower oil temp, cleanliness
- Remember to change these oils more frequently than regular motor oils

For health safety information, please refer to the Safety Data Sheet at REDLINEOIL.COM