



RED LINE D4 ATF



- Our most versatile ATF, use where Dexron III®, Dexron II®, Mercon® and Mercon V® fluids are recommended, for use in automatic, manual transmissions and power steering
- Popular applications: Toyota Type T-III and T-IV, Honda ATF-Z1, NissanMatic D, J & K, Diamond SP-II, SP-III, Mazda ATF M-V, most BMW and Audi/VW automatic transmissions
- Also used with manual transmissions and transaxles like T-5, T-45, T-56 and late-model BMW
- Excellent cold weather operation

RECOMMENDED FOR:

Dexron II®, III® and Dexron IIIH®

Mercon® and Mercon V®

Esso LT71141
(BMW, 93 on 3, 5 and 7 series ZF 5HP transmissions)
(VW/Audi automatic from 1993)

Shell LA2634
(BMW Automatic 98-00 3 series, 94-95 5 series,
98-00 528, 94-00 7 and 8 series)

Shell ATF 3403 M115
(Mercedes 5&6 sp, Jeep NAG-1, Porsche
& Jaguar Automatic)

Texaco ETL7045
(BMW 01 3 series Xi, X5 3.0, Z3, 98-05 3 series,
w/ GM5, 99-00 5 series w/GM5, 04-08 X3 w/GM5)

Texaco ETL8072 B
(BMW 00-05 5 series & X5 w/ GM5)

Idemitsu K17 (Jatco 3100) WSS-M2C922-A1

Honda ATF Z1
(Honda/Acura automatic)

Diamond SP-II & SP-III
(Mitsubishi, Hyundai and Kia automatic)

Castrol Transmatic J, Transmax J, Transmax E,
Pennsoil ATF J, Idemitsu HP, Subaru ATF-HP
(Subaru 05 on WRX, Impreza, Legacy, Outback,
Tribeca & 06 on Forester)

Mazda ATF M-V
(03 on Mazda6, 04 on Mazda3, 06 on Mazda5, 06 on
Ford Fusion w/FNR5 automatic transaxle)

NissanMatic D, J & K

Mobil ATF 3309, JWS 3309, Toyota T-IV and T-III,
T3, T4, ATF JWS 2312D, 3314, 3317. Aisin-Warner
applications:
(96-'97 Supra Turbo, '98 Supra, '00 on Echo, Celica,
'01-'03 Prius, '01-'03 Prius, '02-'05 Camry and 4-cyl.
Solara, Rav 4-4WD '01-'04 Highlander, Rav4, '03-'04
Sequoia, Tundra, Tacoma 2.7L, 3.4L, '03-'04 4-
Runner w/4 speed, '03 Land Cruiser, '05 Tacoma)
(Volvo '01 to '04 C70, '01 on S40, V40, S60, S60R,
'99 on V70, V70R and XC70 w/AW50AWD or AW55-
50SN transaxle)

Dexron and Mercon are registered trademarks owned by
General Motors Corporation and Ford Motor Company,
respectively.

TYPICAL PROPERTIES:

SAE Viscosity Grade (Motor Oil)	0W20
SAE Viscosity Grade (Gear Oil)	70W80
Vis @ 100°C, cSt	7.5
Vis @ 40°C, cSt	35.4
Viscosity Index	188
Pour Point, °C	-51
Brookfield Viscosity @ -40°C, Poise	52

PACKAGE SIZES:

- 30504 - D4 ATF - quart
- 30505 - D4 ATF - 1 gallon
- 30506 - D4 ATF - 5 gallon
- 30507 - D4 ATF- 16 gallon
- 30508 - D4 ATF- 55 gallon

ABOUT RED LINE AUTOMATIC TRANSMISSION FLUIDS

- Red Line offers the widest selection of full-synthetic ATF on the market today
- Each offer improved thermal stability, maintain viscosity levels and feature lower volatility while providing the required frictional characteristics of each fluid's OEM-style replacement
- Reduced oxidation and lower volatility at high temperature
- Allows high-temp operation without varnishing valves and clutches
- Extended drain intervals

For health safety information, please refer to the Safety Data Sheet at REDLINEOIL.COM