

# PRODUCT INFORMATION



## VALVOLINE™ ULV® FULL SYNTHETIC TRANSMISSION FLUID

Valvoline ULV Full Synthetic Automatic Transmission Fluid (ATF) is specifically formulated for today's technologically sophisticated high-speed transmissions that require ultra-low viscosity (ULV) fluids. Valvoline ULV ATF is formulated with premium synthetic base stocks, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers to meet the performance requirements of the latest 9 & 10 speed transmission designs, including the Ford\* 10R80 found in select Ford F-150 and Raptor Trucks.

### The Valvoline ULV Transmission Fluid Advantages:

- Premium full synthetic fluid to achieve low viscosity and minimize deposits
- Excellent thermal and oxidation performance
- Excellent anti-shudder durability
- Excellent anti-wear performance to prevent gear wear
- Excellent metal-metal friction protection
- Designed to provide excellent torque transfer

### **\*Recommended in applications requiring Dexron ULV or Mercon ULV Fluids:**

Ford® 10R60
Ford® 10R80
GM® 10L80 and 10L90

### **Typical Properties:**

	<b>ULV</b>
KV100 (cSt)	4.45
KV40 (cSt)	19.41
Viscosity Index	146
Pour Point, C°	-57
Specific Gravity @ 60°F	0.848
Brookfield Viscosity @ -40°C, cP	4,780
Appearance	Red

\* Registered Trademark of Ford Motor Company and  
Registered Trademark of General Motors Corporation

Effective Date:  
9/30/20

Author's Initials:  
LK